




Capacities		Metric	Imperial
Max. capacity		3628.70 kg	8000 lb
Max. lifting height		12.96 m	42 ft 6 in
Max. outreach		8.69 m	28 ft 6 in
Veight and dimensions			
Overall length to carriage	l11	6.30 m	20 ft 8 in
Overall length (with forks)	l1	7.51 m	24 ft 8 in
Overall width	b1	2.48 m	8 ft 2 in
Overall height	h17	2.44 m	8 ft
Vheelbase	у	3.50 m	11 ft 6 in
Ground clearance	m4	0.46 m	1 ft 6 in
Overall cab width	b4	0.95 m	3 ft 1 in
ilt-up angle	a4	34 °	34 °
ilt-down angle	a5	96 °	96°
xternal turning radius	Wa3	4 m	13 ft 1 in
Inladen weight		10864 kg	23951 lb
yres type		Pneumatic	Pneumatic
Forks length / width / section	l / e / s	1219 mm x 101 mm / 50.80 mm	48 in x 4 in / 2 in
rame levelling longitudinal +/-	1, 2, 2	10 °	10 °
Performances			.0
ifting		11 s	11 s
owering		6 s	6 s
extension		17 s	17 s
Retraction		11 s	11 s
Crowd		4 s	4 s
Dump		6 s	6 s
ingine		0.5	0.3
ingine brand		Deutz	Deutz
ingine norm		Tier 4 final	Tier 4 final
ingine model		TCD 3.6 L4	TCD 3.6 L4
Number of cylinders / Capacity of cylinders		4 - 3600 cm <sup>3</sup>	4 - 220 in <sup>3</sup>
C. Engine power rating - Power (kW)		74 Hp / 55 kW	74 Hp / 55 kW
Max. torque / Engine rotation		390 Nm @ 2300 rpm	288 ft/lbs @ 2300 rpm
Transmission		370 Nill @ 2300 Ipill	20011/103 @ 23001pm
ransmission type		Powershift	Powershift
lumber of gears (forward / reverse)		5 / 3	5 / 3
Max. travel speed		37 km/h	20 mi/h
Parking brake		SAHR	SAHR
Service brake		Wet disc brakes	Wet disc brakes
lydrau lics	_	wet disc brakes	Wet disc brakes
-		Axial piston	Axial piston
lydraulic pump type		151 l/min-275.80 bar	40 US gpm-4000 PSI
lydraulic flow / Pressure		151 t/111111-27 5.80 Dai	40 03 gpiii-4000 P3i
ank capacities		8.51 l	2 HC mal
ngine oil		8.51 l 136.30 l	2 US gal
lydraulic oil			36 US gal
uel tank		144 l	38 US gal
loise and vibration		00 15	
loise at driving position (LpA)		80 dB	80 dB
Aiscellaneous (Table 1)			
Steering wheels (front / rear)		2 / 2	2 / 2
Steering wheels (front / rear) Drive wheels (front / rear)		2 / 2 2 / 2	2 / 2 2 / 2

## TH8-42 M74 - NEW - Load chart

## Machine on tyres with forks Imperial







Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend